

NORBAR TORQUE TOOLS

TRUKTORQUE™



- Torque from 200 N.m to 1000 N.m (147-738 lbf.ft)
- Free running speed of 140 rpm for rapid bolt run-down
- The integral 'banana' shaped sliding reaction arm is specifically designed to reach rear recessed wheel nuts and across front wheel covers
- The reaction socket is spring loaded to locate onto the next available nut for reaction
- Robust and lightweight, quick and easy to operate
- Compatible with most trucks including:
 - DAF • FORD • FREIGHTLINER • ISUZU • IVECO •
 - KENWORTH • MACK • MAN • MAZDA • MERCEDES •
 - NISSAN • RENAULT • SCANIA • STERLING • VOLVO •
 - WESTERN STAR • WHITE
- Adjustable centres to suit all of these truck wheel hole combinations

Wheel Stud PCD (mm)	Hole Qty	Nut A/F (mm)
335	10	30-33
285.75	10	30-33
285	8	30-33
275	8	30-33
225	10	30-33

- Weight 9.4kg, length 500mm
- Available as ¾" drive (Part number 18162.B06) and 1" drive (P/N 18162.B08)



For more details on all Norbar products please contact:

NORBAR TORQUE TOOLS LTD
 Beaumont Road, Banbury, Oxfordshire OX16 1XJ
 UNITED KINGDOM
 Tel + 44 (0)1295 753600
 Email enquiry@norbar.com

Take Pride – Torque Norbar

www.norbar.com