

Slimline™ Torque Wrench Model SLO Fixed Head and Torque Handles

- Accuracy exceeds all international standards.
- Unmistakable signal when set torque is reached.
- Traceable calibration certificate supplied to satisfy ISO 9000:2000 quality systems.
- High quality 72 tooth ratchet allows use in confined spaces.
- Fixed head version has a push through square for left and right handed torque tightening.
- Moulded grip aids correct handle location and operator comfort.

For 1 - 20 N.m ratchet torque wrenches, see the TruTorque range on page 13.



Adjustable Wrenches - Fixed Head

Model	Square Drive	Part No.	Range		Ratchet Diameter	Engagements per revolution	Length	Weight
	in		N.m	lbf.in	mm		mm	Kg
SLO Fixed	3/8	11035	1 – 20	10 – 180	-	-	211	0.4
SLO Fixed	3/8	11125	4 – 20	40 – 180	-	-	213	0.4

Adjustable Torque Handles

Model	End Fitting	Part No.	Range		Length	Weight
			N.m	lbf.in	mm	Kg
SLO TH	16mm Spigot	11036	1 – 20	10 – 180	207	0.4
SLO TH	16mm Spigot	11126	4 – 20	40 – 180	210	0.4
SLO TH	9x12mm Female	11122	4 – 20	40 – 180	205	0.4

Slimline™ Torque Wrench Model SLO 'P' Type

- Torque Handle versions are available for both 16mm spigot and 9 x 12mm fittings.
- Production 'P' type versions are designed to discourage unauthorised alteration.
- 'P' Type versions have no scale. These wrenches must be set against a torque testing device such as Norbar's Professional Torque Tester (see page 68).



Torque Handles Production 'P' Types

Model	End Fitting	Part No.	Range		Length	Weight
			N.m	lbf.in	mm	Kg
SLO THP	16mm Spigot	11090	1 – 20	10 – 180	207	0.4
SLO THP	9x12mm Female	11088	1 – 20	10 – 180	203	0.4



16mm Spigot



9x12mm Female

Available Fittings

See pages 28 & 29



Fixed Head



Ratchet Head

Ratchet and Fixed Head - Production 'P' Types

Model	Square Drive	Part No.	Range		Ratchet Diameter	Engagements per revolution	Length	Weight
			N.m	lbf.in	mm		mm	Kg
SLO 'P'	¼	11085	1 – 20	10 – 180	29	72	218	0.4
SLO 'P'	⅜	11086	1 – 20	10 – 180	29	72	218	0.4
SLO Fixed	⅜	11089	1 – 20	10 – 180	-	-	211	0.4