

# ENGINEER TO ORDER

SPECIAL PROJECT INFORMATION SHEET



<b>Project Description</b>	Special 19mm A/F Hexagon Output Drive for PTM-72		
<b>Date created</b>	17 December 2015	<b>Project Number</b>	Q2784

## INTRODUCTION & APPLICATION

Pneutorque PTM-72 to tighten a 19mm A/F hexagon socket head cap-screw to 920 N.m maximum torque, with maximum rigidity and minimum length build-up.

## SOLUTION

Special 19mm A/F hexagon output drive for Pneutorque PTM-72 with standard spline and retaining screw, Part # Q2784.72.19.



## TECHNICAL SPECIFICATION / DATA HIGHLIGHTS

No adapters are required.

The tool can be easily converted back to standard by unfastening the output drive retaining capscrew and exchanging the hexagon output drive with the standard square drive.

The following is a guide of other popular sizes that can be engineered to order: -

Hex A/F	Hex A/C	Max torque N.m			
		PTM-52	PTM-72	PTM-92	PTM-119
mm	mm				
17	19.6	675	630	630	630
19	21.9	800	920	920	920
22	25.4	800	1475	1475	1475
24	27.7	800	1935	1935	1935
27	31.2	800	2785	2785	2785
	Hex Length mm	23	23	40	40

The above and other sizes can be quoted on request.