

HandTorque® Standard Series

Model	HT 1/5	HT 2/5	HT 2/25	HT 2/25 AWUR	HT 5/5	HT 5/25	HT 5/25 AWUR	HT 6/5	HT 6/25	HT 6/25 AWUR	HT 6/125 AWUR
Part Number/s	16010	16012.HD	16034.HD	16089.HD	16014	16028	16090	16016	16024	16092	16093
Multiplication Ratio	5:2:1	5:2:1	27:1	25:1	5:2:1	25:1	27:1	5:2:1	27:1	27:1	135:1
Input Square	½"	¾"	½"	½"	¾"	½"	½"	¾"	½"	½"	½"
Output Square	¾"	1"	1"	1"	1"	1"	1"	1½"	1½"	1½"	1½"
Maximum Torque Output	N-m	1,700	1,700	1,700	1,700	3,400	3,400	3,400	3,400	3,400	3,400
	lbf-ft	1,254	1,254	1,254	1,254	2,508	2,508	2,508	2,508	2,508	2,508
Dimensions (mm)	ØD	108	108	108	108	119	119	119	119	119	119
	H	83	98	98	114	106	127	132	106	128	159
	L	303	303	303	303	355	355	355	355	355	355
	R1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	R2 min.	83	83	83	83	86	86	86	86	86	86
	R2 max.	216	216	216	216	263	263	263	263	263	263
Tool Weight (kg)	3	3.2	4.6	6.7	4.7	6.4	7.5	4.7	6.4	7.5	9
Reaction Weight (kg)	2.2	2.2	2.2	2.2	2.5	2.5	2.5	2.5	2.5	2.5	2.5

Model	HT 7/5	HT 7/25	HT 7/25 AWUR	HT 7/125 AWUR	HT 9/25	HT 9/25 AWUR	HT 9/125 AWUR	HT 11/25	HT 11/125 AWUR	HT 13/125 AWUR
Part Number/s	16067	16018	16065	16068	16059	16070	16071	16082	16049	16053
Multiplication Ratio	5:2:1	27:1	27:1	135:1	27:1	27:1	135:1	27:1	1325:1	135:1
Input Square	¾"	½"	½"	½"	¾"	¾"	½"	¾"	½"	½"
Output Square	1½"	1½"	1½"	1½"	1½"	1½"	1½"	2½"	2½"	2½"
Maximum Torque Output	N-m	6,000	6,000	6,000	9,500	9,500	9,500	20,000	20,000	47,500
	lbf-ft	4,425	4,425	4,425	7,007	7,007	7,007	14,751	14,751	35,034
Dimensions (mm)	ØD	144	144	144	184	184	184	212	212	315
	H	136	157	162	188	166	162	182	208	235
	L	423	423	423	423	448	448	448	609	609
	R1	84	84	84	84	84	84	84	N/A	N/A
	R2 min.	150	150	150	150	175	175	175	320	320
	R2 max.	331	331	331	331	351	351	351	500	500
Tool Weight (kg)	8.1	9.6	10.7	12.2	16.3	17.4	18.9	31.7	32.1	95.2
Reaction Weight (kg)	6.3	6.3	6.3	6.3	8.3	8.3	8.3	13.3	13.3	6.9

