

# PneuTorque<sup>®</sup>

## PTS<sup>™</sup> Series

Model	PTS <sup>™</sup> -52-500	PTS <sup>™</sup> -52-800	PTS <sup>™</sup> -72-1000	PTS <sup>™</sup> -72-1350	PTS <sup>™</sup> -72-2000	PTS <sup>™</sup> -80-2700	PTS <sup>™</sup> -92-4000	PTS <sup>™</sup> -119-7000	
Part Number/s	180241.B06	180242.B06	180243.B06	180244.B08	180245.B08	180246.B08	180250.B08	180249.B12	
Torque Range	N-m	100 - 500	160 - 800	200 - 1000	270 - 1350	400 - 2000	540 - 2700	800 - 4000	1400 - 7000
	lbf-ft	74 - 370	118 - 590	147 - 738	200 - 1000	295 - 1475	398 - 1991	590 - 2950	1030 - 5200
Square Drive	¾"	¾"	¾"	1"	1"	1"	1"	1½"	
Output Speed (rpm)	35.5	25.7	20.4	14.7	9.2	7.3	5.3	2.6	
Dimensions (mm)	ØD max.	52	52	72	72	72	80	92	119
	H1	30	30	30	30	30	30	30	30
	H2	243	243	243	243	243	243	243	243
	L	264	264	292	292	325	291	343	369
	R1	59	59	74	74	74	74	74	90
	R2 min.	71	71	124	124	124	124	125	162
R2 max.	131	131	165	165	165	165	175	210	
Tool Weight (kg)	4.2	4.2	6.2	6.2	6.6	6.2	8.59	12.80	
Reaction Weight (kg)	0.9	0.9	1.4	1.4	1.4	1.4	2.5	4	

