

PneuTorque® Standard Series - Remote Manual Two Speed

Model	PT 1	PT 1	PT 1A	PT 1A	PT 2	PT 5	PT 6	PT 7	PT 9	PT 11	PT 12	PT 13	PT 14	PT 15	PT 16	PT 17	PT 18	
Part Number/s	16031.XMTS	16011.XMTS	16098.XMTS	16097.XMTS	16013.XMTS	16015.XMTS	16017.XMTS	16066.XMTS	16072.XMTS	16046.XMTS	18086.XMTS	16052.XMTS	16045.XMTS	18089.XMTS	18090.XMTS	18088.XMTS	16054.XMTS	
Torque Range	N-m	160 - 680	160 - 680	270 - 1200	270 - 1200	515 - 1700	880 - 3400	880 - 3400	1762 - 6000	2710 - 9500	4400 - 20000	9500 - 34000	13550 - 47000	22375 - 100000	40000 - 150000	55000 - 200000	70000 - 250000	85000 - 300000
	lbf-ft	120 - 500	120 - 500	200 - 900	200 - 900	380 - 1250	650 - 2500	650 - 2500	1300 - 4500	2000 - 7000	3250 - 14700	7000 - 25000	10000 - 35000	16500 - 73500	29500 - 110500	40500 - 147500	51500 - 184500	62500 - 221500
Square Drive	¾"	1"	¾"	1"	1"	1"	1½"	1½"	1½"	2½"	2½"	2½"	3½"	N/A	N/A	N/A	N/A	
Output Speed (rpm)	150	150	75	75	45	25	25	12.5	9	6	2.5	1.5	1	0.5	0.4	0.35	0.3	
Dimensions (mm)	∅D	108	108	108	108	119	119	144	184	212	248	315	315	*	410	410	520	
	H	356	356	356	356	356	399	400	429	425	501	542	576	*	786	859	856	
	L	303	303	303	303	303	355	355	423	448	609	325	341	*	N/A	N/A	N/A	
	R1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	84	84	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	R2 min.	83	83	83	83	83	86	86	150	175	320	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	R2 max.	216	216	216	216	216	263	263	331	351	500	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Tool Weight (kg)	14.1	14.1	14.6	14.6	14.6	17.5	17.5	23.2	27.9	42.1	53.3	105.7	122.9	*	270	285	380	
Reaction Weight (kg)	2.2	2.2	2.2	2.2	2.2	2.5	2.5	6.3	8.3	13.3	6.5	6.9	10.4	N/A	N/A	N/A	N/A	

* Available on request

