

PneuTorque® Standard Series - Remote Single Speed

Model	PT 1	PT 1	PT 1A	PT 1A	PT 2	PT 5	PT 6	PT 7	PT 9	PT 11	PT 12	PT 13	PT 14	
Part Number/s	16031.X	16011.X	16098.X	16097.X	16013.X	16015.X	16017.X	16066.X	16072.X	16046.X	18086.X	16052.X	16045.X	
Torque Range	N-m	160 - 680	160 - 680	270 - 1200	270 - 1200	515 - 1700	880 - 3400	880 - 3400	1762 - 6000	2710 - 9500	4400 - 20000	9500 - 34000	13550 - 47000	22375 - 100000
	lbf-ft	120 - 500	120 - 500	200 - 900	200 - 900	380 - 1250	650 - 2500	650 - 2500	1300 - 4500	2000 - 7000	3250 - 14700	7000 - 25000	10000 - 35000	16500 - 73500
Square Drive	¾"	1"	¾"	1"	1"	1"	1½"	1½"	1½"	2½"	2½"	2½"	3½"	
Output Speed (rpm)	30	30	15	15	9	5	5	2.5	1.8	1.2	0.5	0.3	0.2	
Dimensions (mm)	ØD	108	108	108	108	119	119	144	184	212	248	315	315	
	H	270	270	270	270	270	313	314	343	340	415	456	490	563
	L	303	303	303	303	303	355	355	423	448	609	325	341	341
	R1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	84	84	N/A	N/A	N/A	N/A
	R2 min.	83	83	83	83	83	86	86	150	175	320	N/A	N/A	N/A
	R2 max.	216	216	216	216	216	263	263	331	351	500	N/A	N/A	N/A
Tool Weight (kg)	10.6	10.6	11.1	11.1	11.1	14	14	17.9	24.4	38.6	49.8	102.2	119.4	
Reaction Weight (kg)	2.2	2.2	2.2	2.2	2.2	2.5	2.5	6.3	8.3	13.3	6.5	6.9	10.4	

