

Slimline™ Torque Wrench Model SLO Fixed Head and Torque Handles

- Accuracy exceeds all international standards.
- Unmistakable signal when set torque is reached.
- Traceable calibration certificate supplied to satisfy ISO 9000:2000 quality systems.
- Fixed head version has a push through square for left and right handed torque tightening.
- Moulded grip aids correct handle location and operator comfort.

For 1 - 20 N.m ratchet torque wrenches, see the TT range on page 13.



Adjustable Wrenches - Fixed Head

| Model | Square Drive | Part No. | Range | | Length | Weight |
|-----------|---------------|----------|--------|----------|--------|--------|
| | in | | N.m | lbf.in | mm | Kg |
| SLO Fixed | $\frac{3}{8}$ | 11035 | 1 – 20 | 10 – 180 | 211 | 0.4 |
| SLO Fixed | $\frac{3}{8}$ | 11125 | 4 – 20 | 40 – 180 | 213 | 0.4 |

Adjustable Torque Handles

| Model | End Fitting | Part No. | Range | | Length | Weight |
|--------|---------------|----------|--------|----------|--------|--------|
| | | | N.m | lbf.in | mm | Kg |
| SLO TH | 16mm Spigot | 11036 | 1 – 20 | 10 – 180 | 207 | 0.4 |
| SLO TH | 16mm Spigot | 11126 | 4 – 20 | 40 – 180 | 210 | 0.4 |
| SLO TH | 9x12mm Female | 11122 | 4 – 20 | 40 – 180 | 205 | 0.4 |

Slimline™ Torque Wrench Model SLO 'P' Type

- Torque Handle versions are available for both 16mm spigot and 9 x 12mm fittings.
- Production 'P' type versions are designed to discourage unauthorised alteration.
- 'P' Type versions have no scale. These wrenches must be set against a torque testing device such as Norbar's Professional Torque Tester (see page 68).



Torque Handles Production 'P' Types

| Model | End Fitting | Part No. | Range | | Length | Weight |
|---------|---------------|----------|--------|----------|--------|--------|
| | | | N.m | lbf.in | mm | Kg |
| SLO THP | 16mm Spigot | 11090 | 1 – 20 | 10 – 180 | 207 | 0.4 |
| SLO THP | 9x12mm Female | 11088 | 1 – 20 | 10 – 180 | 203 | 0.4 |



16mm Spigot



9x12mm Female

Available Fittings

See pages 28 & 29



Fixed Head



Ratchet Head

Ratchet and Fixed Head - Production 'P' Types

| Model | Square Drive | Part No. | Range | | Ratchet Diameter | Engagements per revolution | Length | Weight |
|-----------|--------------|----------|--------|----------|------------------|----------------------------|--------|--------|
| | in | | N.m | lbf.in | mm | | mm | Kg |
| SLO 'P' | ¼ | 11085 | 1 – 20 | 10 – 180 | 29 | 72 | 218 | 0.4 |
| SLO 'P' | ⅜ | 11086 | 1 – 20 | 10 – 180 | 29 | 72 | 218 | 0.4 |
| SLO Fixed | ⅜ | 11089 | 1 – 20 | 10 – 180 | - | - | 211 | 0.4 |