


NORBAR TORQUE TOOLS WET PIPE CONNECTOR CLAMP TORQUE TOOL



Norbar have developed a torque multiplier specifically for actuating wet pipe connector clamps requiring torques up to 63,000 N.m. The tool is mainly constructed of high strength aluminium to keep the weight within the limits of a standard ROV.

- Output torques up to 63,000 N.m (46,500 lbf.ft)
- Reaction to customers' requirements
- Input is API 17D Class 4 rotary torque receptacle. 1.5" male square drive. Conforms to ISO 13628-8:2002(E)
- Input torque 2700 N.m (2000 lbf.ft) maximum
- 3000 metre depth rating
- Integrated pressure compensation
- Manufactured from high strength lightweight materials to allow manipulation using a standard ROV
- Supplied with manipulator handles for both vertical & horizontal operation
- Typical tool weight is 94kg in air, 60kg in salt water
- Supplied in aluminium Euro case with custom foam insert



For more details on all Norbar products please contact:

NORBAR TORQUE TOOLS LTD
Wildmere Road, Banbury,
Oxfordshire OX16 3JU
UNITED KINGDOM
Tel + 44 (0)1295 753600
Email enquiry@norbar.com

Take Pride – Torque Norbar

www.norbar.com